

Getting Started · Deployment

Generated Tue, Sep 22, 2026 12:12 PM · Single page

Deployment

Production deployment guide for the multi-tenant CRM.

Architecture in production

[Diagram omitted in PDF — open this page in the online docs to view it.]

You need **three** long-running concerns:

1. **HTTP** — PHP-FPM / Octane / shared hosting endpoint
 2. **Queue worker** — channels + default
 3. **Scheduler** — `php artisan schedule:run` every minute
-

Pre-deploy checklist

- ☐ `APP_ENV=production, APP_DEBUG=false`
 - ☐ Strong `APP_KEY` (never commit)
 - ☐ `APP_URL` is the public HTTPS URL
 - ☐ `SESSION_SECURE_COOKIE=true` behind HTTPS
 - ☐ Real mailer (`smtp` / `SES` / `Postmark` / `Resend`) — not `log`
 - ☐ `QUEUE_CONNECTION=database` (or Redis if you configure it)
 - ☐ `META_APP_SECRET` set if using Facebook Lead Ads / WhatsApp
 - ☐ Database backups configured
 - ☐ SSL certificate valid for webhook callbacks
-

Deploy steps (typical VPS)

```
cd /var/www/crm
git pull origin main

composer install --no-dev --optimize-autoloader
npm ci && npm run build

php artisan migrate --force
php artisan permissions:sync
php artisan config:cache
php artisan route:cache
php artisan view:cache
php artisan event:cache    # if applicable

# restart PHP-FPM / Octane / queue workers after deploy
```

Always run migrations **before** relying on new features. For MySQL, ensure prior channel migrations completed cleanly (partial tables from failed runs must be cleaned up — see [Troubleshooting](#)).

Queue worker (required)

Channel webhooks enqueue `ProcessChannelWebhookJob` on the `channels` queue.

```
php artisan queue:work --queue=channels,default --sleep=1 --tries=5 --timeout=90
```

Recommended: supervise with Supervisor / systemd so the worker restarts on failure and after deploys.

Example Supervisor program:

```
[program:crm-worker]
process_name=%(program_name)s_%(process_num)02d
command=php /var/www/crm/artisan queue:work --queue=channels,default --sleep=1 --tries=5 --timeout=90
autostart=true
autorestart=true
user=www-data
numprocs=1
redirect_stderr=true
stdout_logfile=/var/www/crm/storage/logs/worker.log
```

After code deploys: `php artisan queue:restart`.

Details: [Queues](#).

Scheduler (required)

Add a system cron entry:

```
* * * * * cd /var/www/crm && php artisan schedule:run >> /dev/null 2>&1
```

This drives lead/task reminders, trial notices, pruning, and platform alert jobs.

Details: [Scheduler](#).

Web server notes

- Document root: `public/`
 - Allow `POST` (and `GET` for Meta verify) to:
 - `/webhooks/leads/website`
 - `/webhooks/channels/{uuid}`
 - These paths are CSRF-exempt in `bootstrap/app.php`.
 - Prefer `HTTPS` end-to-end; Meta requires a public `HTTPS` callback for WhatsApp / Lead Ads.
-

Zero-downtime tips

1. Put app in maintenance: `php artisan down` (optional).
 2. Deploy code + `composer install --no-dev`.
 3. Migrate.
 4. Rebuild caches.
 5. `php artisan queue:restart`.
 6. `php artisan up`.
-

Health checks

Check	How
App up	GET /up (Laravel health)
Scheduler alive	Super Admin platform settings / scheduler_last_run_at heartbeat (every 5 minutes)
Queues draining	jobs table not growing unbounded; worker logs show processed jobs
Webhooks	Channel detail → Recent events; Meta webhook delivery logs

Security

- Never commit .env or secrets shared in chat — rotate Meta tokens/App Secret if exposed.
 - Restrict Super Admin accounts tightly.
 - Keep WEBSITE_LEAD_WEBHOOK_SECRET server-side only.
 - Review failed webhook events and activity logs regularly.
-

Related

- [Installation](#)
- [Configuration](#)
- [CI/CD \(recommended\)](#)